



ELECTRIC CABLE SERVICE DUCTING

SMALL BORE SERVICE DUCTING



Small bore service ducting for the protection of electric cables including signal and data cable infrastructure.

SPECIFICATION OVERVIEW

- ENA TS 12-24 Issue 4 2021
- PE-HD - Black

BESPOKE UPON REQUEST, MOQs APPLY

- PE100 - Red
- PE100 - Orange
- PE100 - Green
- PE100 - Purple

OD	ID	Classification	Material
37mm	32mm	C3	PE-HD/PE100
44mm	38mm	C3	PE-HD/PE100
60mm	50mm	C3	PE-HD/PE100

Nom size (mm)	Max OD (mm)	Mean weight (kg/m)	Mean bore (mm)
37	37.2	0.26	32
44	44.3	0.36	38
60	60.4	0.82	50

LENGTHS

Pipes ≤ 60mm in diameter will be supplied in coil lengths of 25, 50, 100, 150m. Other lengths can be produced at customers request.

MARKINGS

All products will be marked on one side with characters at least 6mm high in a contrasting colour to the pipe material ≤60mm in diameter. Markings repeated every metre.

The following identification and traceability marks are printed once every metre;

- Manufacturers identification: SIMONA Peak Pipe Systems
- Application Identifier: "ELECTRIC CABLE DUCT"
- Material designation: PE-HD
- Classification: C3
- Standard number: ENA TS 12-24
- Outside diameter: 60mm (example)
- Manufacturing code: (Contains date)

